

Ultra-Cool™ Wide Temperature Recirculating Chillers

The Ultra-Cool delivers:

- Large capacity recirculators for maximum cooling and heating from -40°C to +130°C
- Ideal for applications that require high capacity cooling
- Air-cooled for convenient system placement
- The widest precision-controlled temperature range available

Ultra-Cool recirculating chillers are specifically designed for continuous, 24-hour duty, delivering industrial capacity fluid circulation for applications that require temperatures from -40°C to +130°C. With 10kW of heat, Ultra-Cool offers the widest precision-controlled temperature range in the industry.

Ultra-Cool's high capacity cooling and pumping abilities make it ideal for reaction vessel applications, replacements for equipment water cooling, or as dedicated coolers for large water-cooled equipment or instrumentation.

Standard units are air-cooled for convenient system placement, and include an internal high-pressure bypass to protect your equipment. Ultra-Cool can also be supplied as a water-cooled unit to minimize heat transfer to the installation site.

Features at a glance:

- Standard digital/RS232 control permitting precision control of all temperature parameters
- ±0.5°C stability
- Wide temperature ranges:
 - 15°C to +30°C (standard)
 - 40°C to +130°C
- Mechanical refrigeration, air or water-cooled
- Compact footprint



Call **800-824-0400** or
visit www.ftssystems.com

Applications:

- > Reaction vessels
- > Lasers
- > AA graphite furnace
- > Condenser cooling
- > Diffusion pumps
- > Turbo-molecular pumps
- > Vacuum systems
- > GC/MS
- > Electron microscopes
- > ICP
- > Plasma etch equipment
- > Sputtering systems
- > Power supplies



Options for UC500, UC500LT, UC750, UC750LT

Heater Options:

Heaters are only available for models UC500LT and UC750LT

- 4kW to 130°C
- 10kW to 130°C (460V or 380V only) (20 GPM pump only)

Pump Options:

- 8 gpm, 86 psi positive displacement
- 20 gpm @ 45 psi centrifugal

Cooling Option:

- Water-cooled system

Electrical Options:

- 220V/50 Hz/3 ph*
- 460V/60 Hz/3 ph
- 380V/50 Hz/3 ph*

* For 50 Hz units, decrease heat removal by 17%.

Controller Option:

- Standard digital control has PID, RS232 computer interface and low fluid indicator.
- Deluxe digital control (required for +130°C units) has PID RS232, external temperature sensor, and an alarm package including: low fluid, low flow, and over-temp with an external contact closure.

Fluid Selection Facts

For best pumping or stirring results, choose a fluid medium with a kinematic viscosity of 20 centistokes or less over the full operating temperature range. Remember, the heat exchanger in the recirculating cooler may be several degrees colder than your process.

Ultra-Cool Model Specifications

		UC500	UC500LT ¹	UC750	UC750LT ¹
Heat Removal (watts/BTUs)	+20°C	15500/52850	12500/42625	24000/81910	17000/57970
	+10°C	14100/48080	12100/41295	18000/61435	16000/54560
	0°C	11100/37850	12000/40955	14000/47780	15000/51150
	-10°C	6800/23202	8200/27960	9000/30690	11000/37510
	-15°C	-	7300/24915	-	9000/30690
	-20°C	-	6000/20460	-	8000/27280
	-30°C	-	3600/12285	-	4500/15345
Temperature Range C°		-15 to 30	-40 to 30	-15 to 30	-40 to 30
Reservoir(liters):		21	21	21	21
Compressor:		6 hp	6 hp	7 1/2 hp	7 1/2 hp
Controls Standard:		Digital/RS232	Digital/RS232	Digital/RS232	Digital/RS232
Option:		Deluxe digital	Deluxe digital	Deluxe digital	Deluxe digital
Stability ±°C:		0.5	0.5	0.5	0.5
Heater (optional):		-	130°C/4 kW or 10 kW ²	-	130°C/4 kW or 10 kW ²
Pump Standard:Centrifugal		20 gpm @ 45 psi	20 gpm @ 45 psi	20 gpm @ 45 psi	20 gpm @ 45 psi
Option:Positive Displacement		8 gpm to 86 psi	8 gpm to 86 psi	8 gpm to 86 psi	8 gpm to 86 psi
Dimensions:	inches	37 x 37 x 41	37 x 37 x 41	37 x 37 x 41	37 x 37 x 41
W x D x H	cm	94 x 94 x 104	94 x 94 x 104	94 x 94 x 104	94 x 94 x 104
Weight:	lbs/kg	700/318	700/318	800/363	800/363
Electrical:		208/230V 60Hz/3ph	208/230V, 60Hz/3ph	208/230V, 60Hz/3ph	208/230V, 60Hz/3ph
Option:		220V/50 Hz/3 Ph 380V/50 HZ/3 Ph 460V/60 Hz/3 Ph	220V/50 Hz/3 Ph 380V/50 HZ/3 Ph 460V/60 Hz/3 Ph	220V/50 Hz/3 Ph 380V/50 HZ/3 Ph 460V/60 Hz/3 Ph	220V/50 Hz/3 Ph 380V/50 HZ/3 Ph 460V/60 Hz/3 Ph

*Specifications noted above are dependent on fluid choice, fluid temperatures, ambient temperature and electrical supply. Please contact the factory to further discuss your requirements.

1. When air-cooled units are manufactured with the heater option, derate the heat removal by 10%.
2. 4kW heat option for UC500LT and UC750LT adds 11 amps to utility requirement. 10kW heat option for UC500LT and UC750LT with 380 or 460 volts adds 12 amps to utility requirement.



Committed to Product Excellence...and Continuous Support

SP Industries

PO Box 158 3538 Main Street Stone Ridge, NY 12484 USA
800.824.0400 Phone : 845.687.0071 Fax: 845.687.7481 www.ftssystem.com

VirTis FTS Hull Wilmad | LabGlass Hotpack Genevac

SP Industries Corporate Headquarters:

935 Mearns Road Warminster, PA 18974 USA 800.523.2327 Phone: 215.672.7800 Fax: 215.672.7807 www.SPindustries.com