



Mercaptans

TOTAL Reduced
Sulfur (TRS))

Chroma S

Online monitoring & analysis of
Sulphur compounds by GC/FPD

**Model: C51022**Sulphur Specific Analyser (from ppb to ppm)

- SO_2 / CS_2 / H_2S / COS^*
- Mercaptans (Methyl-SH / Ethyl-SH / Isopropyl-SH / Terbutyl -SH...)
- sulphides (DMS / DMDS / DES...)
- * (COS optional)

Chroma S applications: Odour Control & monitoring

- Stack Emission Monitoring
- CEM - Continuous Emission monitoring
- Ambient Air Monitoring
- Waste Water Treatment Plant
- Gas odorisation & deodorisation
- Impurities in Pure Gas (CO_2 , CH_4 ...)

Chromatotec™ is specialised in VOC, Sulfur and permanent gases analysis at trace and ultra trace levels (ppm, ppb, ppt).
Please visit our website for more details.

Chroma S

Online monitoring & analysis of Sulphur compounds by GC/FPD

Description:

Chroma S is a fully automatic isothermal gas Chromatograph for the analysis & monitoring of sulphur compounds.

Principle:

- Continuous, uninterrupted sampling
- Sample is injected into column oven for separation
- Controlled oven selects optimum temperature based on application
- Detection achieved by a sulphur specific photometric double flame detector

Features:

- The double flame ensures no quenching occurs
- Automatic linearization of compounds
- Identification of compounds is based on their retention time (Elution from the column)
- Automatic data validation as standard with the internal permeation tube

VISTACHROM® software

Chromatotec™ developed software system allows

- Remote monitoring
- Full traceability through archiving of results and QC
- Set up and control of threshold alarms
- Export of data MODBUS / MGS1 / 4-20mA / 0-10V

Options:

- Automatic data transfer through:
 - Modbus or MSG1 communication protocol
 - Analog 4-20mA or 0-10V output
- Hydrogen Generator
- Zero Air Generator
- Multiple stream analysis with Multiplexer
- Dilution system
- Heated lines

Technical specifications:

Compounds analysed:

Specific sulphur compounds analysis

H₂S, Me-SH, Et-SH, Isopropyl-SH, Npropyl-SH, 2-butyl-SH, Terbutyl-SH, DMS, DES, DMDS, COS, CS₂ ...

Detection Limit:

- 4 ppb double Sulphur Compounds (DMDS / CS₂ etc..)
- 7 ppb single Sulphur Compounds (H₂S DMS etc..)

Detection Range: (selectable ppm / ppb)

- 4 ppb to 5 ppm (Low Range)
- 100 ppb to 100 ppm (High Range)

Relative Standard Deviation:

- RSD < 5% on concentration over 24hrs
- RSD < 1% on Retention Time over 24hrs

Data Management:

- Full storage of chromatograms & results
- All analyses date & time stamped individually

Cycle Times:

- Cycle times are dependant on application
- Example: * H₂S plus COS - 200 secs
* Total Sulphur - 600 secs

Gas Supply:

- Carrier Gas - Air or N₂ 3 bar (5ml/min) 1/8"
- Sample Inlet - 1 Bar or ambient pressure (airmopump)
- Detector - H₂ at 2 Bar (70 ml/min) 1/8"
- Air at 3 bar (80 ml/min) 1/8"

Power Supply:

- Main: (230V / 50Hz) or (115V / 60Hz)
- Battery: 24V (as option)
- Consumption: 250W (+50W for computer)

Dimensions and Weight:

- Rack: 482mm (19"), Height: 177,8 mm (4U) or 222 mmm (5U), Depth: 600mm
- Weight: 22 kg (With integrated computer)

For ordering:

- Chroma S
- Chroma S - COS (calib included)
- integrated computer: XXX022
- internal calibration: XXX931

Model:

C51000
C51000-COS
XXX022
XXX031

Chromatotec™ is specialised in VOC, Sulfur and permanent gases analysis at trace and ultra trace levels (ppm, ppb, ppt). Please visit our website for more details.

To contact us: info@chromatotec.com



NORTH AMERICA

CHROMATOTEC Inc.
18333 Egret Bay Blvd, Suite 270,
Houston TX 77058 - USA
Phone: +1 (281) 335 4944
Fax: +1 (281) 335 4943

EUROPE

AIRMOTEC AG SAS
15 rue d'Artiguelongue
33240 Saint-Antoine - FRANCE
Phone: +33 (0) 557 940 626
Fax: +33 (0) 557 940 620

ASIA

CHROMATOTEC Beijing
Room 1806, Building 1,
Wanda Plaza, No.93, Jianguo
Avenue, Chaoyang District,
Beijing 100022 - CHINA
Phone: +86 (0) 105 960 3283